

MEDICAL CYLINDER SPECIFICATIONS



PART #	SERVICE PRESSURE (psi / bar)	WATER CAPACITY (lbs / liters)	DIAMETER (in / mm)	LEGNTH (in / mm)	CYLINDER WEIGHT (lbs / kgs)	OXYGEN (cu ft / liters)
M74	3000 / 207	22.0 / 10.0	7.25 / 184.2	23.7 / 602	28.4 / 12.9	74.0 / 2096
M32	3000 / 207	9.3 / 4.2	4.38 / 111.3	25.4 / 645	10.5 / 4.8	32.0 / 906
M20	3000 / 207	5.7 / 2.6	4.38 / 111.3	16.8 / 427	7.3 / 3.3	20.0 / 566
M12	3000 / 207	3.4 / 1.5	4.38 / 111.3	10.9 / 277	5.1 / 2.3	12.0 / 340
M7.8	3000 / 207	2.1 / .96	4.38 / 111.3	7.8 / 198	3.9 / 1.8	7.8 / 221
M7.5	3000 / 207	2.1 / .95	3.21 / 81.5	11.8 / 300	2.9 / 1.3	7.5 / 212
M265	2216 / 153	102.2 / 46.4	9.80 / 248.9	51.8 / 1316	84.8 / 38.3	265.0 / 7505
M150	2015 / 139	63.7 / 28.9	8.00 / 203.2	47.0 / 1194	48.8 / 22.1	150.0 / 4248
M122	2216 / 153	47.1 / 21.4	8.00 / 203.2	36.2 / 919	39.5 / 17.9	122.0 / 3455
M90	2216 / 153	34.7 / 15.7	7.25 / 184.2	32.6 / 828	30.3 / 13.7	90.0 / 2549
M60	2216 / 153	23.2 / 10.5	7.25 / 184.2	22.9 / 582	22.3 / 10.1	60.0 / 1699
ME	2015 / 139	10.2 / 4.6	4.38 / 111.3	25.4 / 645	7.8 / 3.5	24.0 / 680
M22	2216 / 153	8.5 / 3.9	5.25 / 133.4	16.3 / 413	8.1 / 3.7	22.0 / 623
MD	2015 / 139	6.4 / 2.9	4.38 / 111.3	16.7 / 424	5.4 / 2.5	15.0 / 425
M9	2015 / 139	3.8 / 1.7	4.38 / 111.3	10.9 / 277	3.8 / 1.7	9.0 / 255
M7	2015 / 139	3.0 / 1.4	4.38 / 111.3	9.1 / 231	3.2 / 1.5	7.0 / 198
ML6	2015 / 139	2.5 / 1.2	4.38 / 111.3	7.8 / 198	2.9 / 1.3	6.0 / 170
M6	2216 / 153	2.3 / 1.0	3.21 / 81.5	11.8 / 300	2.3 / 1.0	6.0 / 170
M4	2216 / 153	1.5 / .70	3.21 / 81.5	8.7 / 221	1.7 / .80	4.0 / 113
M2	2216 / 153	.63 / .29	2.50 / 63.5	5.9 / 149	.75 / .34	1.6 / 45

CARBON DIOXIDE CYLINDER SPECIFICATIONS

Part No.	Diameter	Length	Empty Weight	CO ₂ Capacity	Nitrogen Capacity	Water Capacity	Standard Thread Size*
	(in / mm)	(in / mm)	(lbs / kgs)	(lbs / kgs)	(cu ft / liters)	(cu in / lbs / liters)	
B35	8.00 / 203.0	37.8 / 960	35.2 / 16.0	35 / 15.9	100.9 / 2527	1426 / 51.5 / 23.4	1.125-12UNF-2B
B22	8.00 / 203.0	25.1 / 638	24.5 / 11.1	22 / 10.0	63.5 / 1798	901 / 32.5 / 14.7	1.125-12UNF-2B
B20	8.00 / 203.0	23.2 / 589	23.1 / 10.5	20 / 9.1	57.6 / 1631	814 / 29.4 / 13.3	1.125-12UNF-2B
B15	6.89 / 175.0	23.1 / 587	16.2 / 7.3	15 / 6.8	43.3 / 1226	612 / 22.1 / 10.0	1.125-12UNF-2B
B10	6.89 / 175.0	16.5 / 419	12.3 / 5.6	10 / 4.5	29.0 / 821	407 / 14.7 / 6.7	1.125-12UNF-2B
B5	5.25 / 133.4	14.2 / 361	6.3 / 2.9	5 / 2.3	14.5 / 411	203 / 7.4 / 3.4	1.125-12UNF-2B
B2.5	4.38 / 111.3	10.3 / 262	3.2 / 1.5	2.5 / 1.1	7.2 / 204	102 / 3.7 / 1.7	.750-16UNF-2B

