Amerlife
Tel. 6131380 Bogota

VH Series VICTOR® Style

Single Stage with 2 Gauges | Heavy Duty Regulators

UL LISTED

Features :

- Single stage construction
- Forged brass body & bonnet for maximum strength
- Stainless steel diaphragms
- Oxygen Regulator with safety relief valve is set for safe operation
- Sintered metal inlet filter to trap impurities
- No soldered joints, for easy maintenance
- Side entry
- UL Listed
- Net Weight: 2.1kg/each

Specifications :

Model No.	Gas	Max Inlet Pressure (Bar)	Delivery Pressure (Bar)	Working Pressure (Bar)
VH-1.4M-AC	Acetylene	0-28	1.4	0-2
VH-1.4M-LP	Propane	0-28	1.4	0-2
VH-3.5M-LP	Propane	0-28	3.5	0-5
VH-7M-OX	Oxygen	0-315	7	0-14
VH-7M-*	Argon / CO_2 / Nitrogen Hydrogen / Helium / Air	0-315	7	0-14
VH-13M-OX	Oxygen	0-315	13	0-28
VH-13M-*	Argon / CO_2 / Nitrogen Hydrogen / Helium / Air	0-315	13	0-28

* Always specify model number and gas when ordering.
** Inlet and outlet connection will be supplied to suit your requirement.

Conformity with EN ISO 2503

49 Series VICTOR® Style

Single Stage with 1 Gauge | Station & Pipeline Regulators

Features :

- Single stage construction
- Forged brass body & bonnet for maximum strength
- Neoprene diaphragms
- Designed for Americane with gas distribution system for medium to heavy flow applications
- Sintered metal inlet filter to trap impurities
- No soldered joints, for easy maintenance
- Side entry
- DO NOT use on cylinder directly
- Net Weight: 1.6kg/each

Specifications :

Model No.	Gas	Max Inlet Pressure (Bar)	Working Pressure (Bar)
49-1.5M-AC	Acetylene	1.5	0-2.5
49-1.5M-LP	Propane	1.5	0-2.5
49-1.5M-LP	Propane	3.5	0-5
49-4M-LP	Propane	4	0-6
49-10M-OX	Oxygen	10	0-16
49-10M-*	Argon / CO_2 / Nitrogen Helium / Hydrogen / Air	10	0-16
49-15M-OX	Oxygen	15	0-25

* Always specify model number and gas when ordering.
** Inlet and outlet connection will be supplied to suit your requirement.

WT-304 Series WESTERN® Style

Single Stage with 2 Gauges | High Pressure Regulators

Features :

- Single stage construction
- Machined Brass body & housing cap
- Piston type construction
- Sintered metal inlet filter to trap impurities
- No soldered joints, for easy maintenance
- T Screw adjustment
- Side entry
- Net Weight: 2.0kg/each

Specifications :

Model No.	Gas	Max Inlet Pressure	Delivery Pressure	Working Pressure
WT304-70M-OX	Oxygen	315 Bar / 4500 psi	70 Bar / 1000 psi	1400 psi
WT304-70M-*	Argon / Nitrogen Hydrogen / Helium / Air	315 Bar / 4500 psi	70 Bar / 1000 psi	1400 psi
WT304-100M-OX	Oxygen	315 Bar / 4500 psi	100 Bar / 1400 psi	2800 psi
WT304-100M-*	Argon / Nitrogen Hydrogen / Helium / Air	315 Bar / 4500 psi	100 Bar / 1400 psi	2800 psi
WT304-210M-OX	Oxygen	315 Bar / 4500 psi	210 Bar / 3000 psi	4500 psi
WT304-210M-*	Argon / Nitrogen Hydrogen / Helium / Air	315 Bar / 4500 psi	210 Bar / 3000 psi	4500 psi

* Always specify model number and gas when ordering.
** Inlet and outlet connection will be supplied to suit your requirement.

203 Series VICTOR® Style

Single Stage with 2 Gauges | High Pressure Regulators

Features :

- Single stage construction
- Forged brass body & bonnet for maximum strength
- Piston type construction
- External safety relief valve is Standards
- Sintered metal inlet filter to trap impurities
- No soldered joints, for easy maintenance
- T Screw adjustment
- Side entry
- Net Weight: 1.5kg/each

Specifications :

Model No.	Gas	Max Inlet Pressure (Bar)	Delivery Pressure (Bar)	Working Pressure (Bar)
203-30M-OX	Oxygen	0-315	30	0-50
203-30M-AR	Argon	0-315	30	0-50
203-30M-CD	CO_2	0-315	30	0-50
203-30M-N2	Nitrogen	0-315	30	0-50
203-30M-HY	Hydrogen	0-315	30	0-50
203-30M-HE	Helium	0-315	30	0-50
203-30M-AIR	Air	0-315	30	0-50
203-50M-OX	Oxygen	0-315	50	0-70
203-50M-N2	Nitrogen	0-315	50	0-70

* Always specify model number and gas when ordering.
** Inlet and outlet connection will be supplied to suit your requirement.

Amerlife
Tel. 6131380 Bogota

101-LM Series HARRIS® Style

Single stage | Flowgauge Regulators

Features :

- Single stage construction
- Forged brass body for maximum strength
- Chrome bonnet
- Neoprene diaphragms
- Sintered metal inlet filter to trap impurities
- Accurate regulator for gas flow
- No soldered joints, for easy maintenance
- Side entry (Vertical optional)
- MIG/TIG applications for light to medium duty
- Net Weight: 1.2kg/each

Specifications :

Model No.	Gas	Flow (Lt./min)	Flow (SCFH)	Cylinder Pressure (Bar)
101-16LM-AR	Argon	0-16		0-315
101-16LM-CD	CO_2	0-16		0-315
101-30LM-AR	Argon	0-30		0-315
101-30LM-CD	CO_2	0-30		0-315
101-50LM-AR	Argon	0-50		0-315
101-50LM-CD	CO_2	0-50		0-315
101-30CF-AR	Argon		0-30	0-315
101-30CF-CD	CO_2		0-30	0-315
101-50CF-AR	Argon		0-50	0-315
101-50CF-CD	CO_2		0-50	0-315

100-FL Series VICTOR® Style

Single stage | Flowmeter Regulators

Features :

- Single stage construction
- Machined Brass body
- Piston type construction
- Sintered metal inlet filter to trap impurities
- Accurate regulator for gas flow
- No soldered joints, for easy maintenance
- Combination of regulator and flow meter as one unit
- Side entry
- Economy style
- Outlet pressure at 3.5 Bar (Present)
- MIG/TIG applications for light to medium duty
- Option kit available with 10 feet (3m) hose in clamshell packaging
- Net Weight: 1kg/each

Specifications :

Model No.	Gas	Flow (Lt./min)	Flow (SCFH)	Cylinder Pressure (Bar)	10 Feet Hose
100-25FL-AR	Argon	0-25		0-315	W/O
100-25FL-CD	CO_2	0-25		0-315	W/O
100-60CF-AR	Argon		0-60	0-315	W/O
100-60CF-CD	CO_2		0-60	0-315	W/O
100A-60CF-AR	Argon		0-60	0-315	Included
100A-60CF-CD	CO_2		0-60	0-315	Included