

Introducing the First and Only Oxygen and Air Flowmeters with Antimicrobial Product Protection

The antimicrobial-treated rotary knob on these flowmeters will continue to inhibit the growth of odor causing bacteria, mold, mildew, and fungi on the surface of the knobs, and maintain antimicrobial efficacy for the lifespan of the product.

- Built-in product protection prevents growth of microbes on the surface of the product
- Broad Regulatory Approvals including EPA, FDA, NSF, Health Canada, European BDP, Swiss & EFSA
- Gentec flowmeters have a 0-15 LPM flow range, with a minimum of 65 LPM flush flow rate
- Based on non-volatile, naturally-occurring silver
- Long-lasting product protection, lasts the lifetime of the knob
- Environmentally-friendly technology (green product)
- Cradle-to-cradle silver certified
- Novation contract pricing available
- Available in either nickel plated solid brass or aluminum
- Durable polycarbonate hood and metering tube
- Stainless steel ball float
- Flowmeters are all calibrated at 50 psig and 70° F
- Flowmeters are all back-pressured compensated
- Color-coded for air and oxygen
- 5-year warranty (see warranty statement for details)



Agion® is a registered trademark of Agion® Technologies.




FM197B-15L-CH-P

Oxygen Flowmeter w/ Power Take-off & Chemtron Adapter

FM187B-15L-00

FLOWMETER ORDERING INFORMATION

Flowmeter Type Adapter	Air Flowmeter 0-15 LPM	Air Flowmeter w/ Power Take-off	Air Dual Flowmeter 0-15 LPM	Oxygen Flowmeter 0-15 LPM	Oxygen w/ Power Take-off	Oxygen Dual Flowmeter 0-15 LPM
	 <i>Standard Inlet 1/8" NPT Female</i>	 FM187B-15L-00	 FM187B-15L-00-P	 FMD187B-15L-00	 FM197B-15L-00	 FM197B-15L-00-P
 <i>OHMEDA Adapter</i>	FM187B-15L-OH	FM187B-15L-OH-P	FMD187B-15L-OH	FM197B-15L-OH	FM197B-15L-OH-P	FMD197B-15L-OH
 <i>CHEMETRON Adapter</i>	FM187B-15L-CH	FM187B-15L-CH-P	FMD187B-15L-CH	FM197B-15L-CH	FM197B-15L-CH-P	FMD197B-15L-CH
 <i>DISS Hand-Tight Nut & Nipple Adapter</i>	FM187B-15L-DH	FM187B-15L-DH-P	FMD187B-15L-DH	FM197B-15L-DH	FM197B-15L-DH-P	FMD197B-15L-DH
 <i>Diss Nut & Nipple Adapter</i>	FM187B-15L-DS	FM187B-15L-DS-P	FMD187B-15L-DS	FM197B-15L-DS	FM197B-15L-DS-P	FMD197B-15L-DS
 <i>Puritan-Bennett Adapter</i>	FM187B-15L-PB	FM187B-15L-PB-P	FMD187B-15L-PB	FM197B-15L-PB	FM197B-15L-PB-P	FMD197B-15L-PB
 <i>Oxequip Medstar Adapter</i>	FM187B-15L-OE	FM187B-15L-OE-P	FMD187B-15L-OE	FM197B-15L-OE	FM197B-15L-OE-P	FMD197B-15L-OE
 <i>Oxequip Twist Adapter</i>	FM187B-15L-OQ	FM187B-15L-OQ-P	FMD187B-15L-OQ	FM197B-15L-OQ	FM197B-15L-OQ-P	FMD197B-15L-OQ

OPTIONS:

- For aluminum flowmeter, change the B to an A (example: FM197B-15L-OH to FM197A-15L-OH)
- For dual flowmeter with 2 power take-offs, add -2P (example: FMD197B-15L-OH-2P)
- Canadian ISO flowmeters available as well

SPECIFICATIONS

Weight (No Adapter):	Aluminum Body: 4.24 oz/122 gm Brass Body: 6.64 oz/188 gm
Increment:	0-6 LPM in ½ LPM increment, 6-15 LPM in 1 LPM Increment
Flush Flow Rate:	65 LPM (depending on supply flow)
Max Inlet Pressure:	100 psig
PTO Flow Rate:	Over 100 LPM (depending on supply flow)